



- ✓ ทนสารเคมี
- ✓ ทนต่อการหักงอ
- ✓ น้ำหนักเบา
- ✓ ทนสภาพแวดล้อมที่เย็น



NO.	ID (mm)	OD (mm)	Wall Thickness (mm)
1	1.0	2.0	0.50
2	1.0	3.0	1.00
3	1.0	4.0	1.50
4	1.5	3.0	0.75
5	1.5	5.0	1.75
6	2.0	3.0	0.50
7	2.0	3.5	0.75
8	2.0	4.0	1.00
9	2.0	5.0	1.50
10	2.0	6.0	2.00
11	3.0	5.0	1.00
12	3.0	6.0	1.50
13	3.0	7.0	2.00
14	3.0	8.0	2.50
15	4.0	6.0	1.00
16	4.0	7.0	1.50
17	4.0	8.0	2.00
18	4.0	9.0	2.50
19	5.0	6.0	0.50
20	5.0	7.0	1.00
21	5.0	8.0	1.50
22	5.0	9.0	2.00
23	5.0	10.0	2.50
24	5.0	11.0	3.00

Contact Us. Tel: 0 2489 5525 MB : 09 2656 8846 Technical Engineer Tel: 09 8253 9956

LINE@ @ptiglobal Email: ptig_sale2@hotmail.com / ptirubber@hotmail.com Website <https://tuberry.net>



- ✓ ทนสารเคมี
- ✓ ทนต่อการหักงอ
- ✓ น้ำหนักเบา
- ✓ ทนสภาพแวดล้อมที่เย็น



NO.	ID (mm)	OD (mm)	Wall Thickness (mm)
25	6.0	8.0	1.00
26	6.0	9.0	1.50
27	6.0	10.0	2.00
28	6.0	11.0	2.50
29	6.0	12.0	3.00
30	6.0	13.0	3.50
31	7.0	9.0	1.00
32	7.0	10.0	1.50
33	7.0	11.0	2.00
34	7.0	12.0	2.50
35	7.0	13.0	3.00
36	8.0	10.0	1.00
37	8.0	11.0	1.50
38	8.0	12.0	2.00
39	8.0	13.0	2.50
40	8.0	14.0	3.00
41	9.0	12.0	1.50
42	9.0	13.0	2.00
43	9.0	14.0	2.50
44	9.0	15.0	3.00
45	10.0	12.0	1.00
46	10.0	13.0	1.50
47	10.0	14.0	2.00
48	10.0	15.0	2.50
49	10.0	16.0	3.00

Contact Us. Tel: 0 2489 5525 MB : 09 2656 8846 Technical Engineer Tel: 09 8253 9956

LINE@ @ptiglobal Email: ptig_sale2@hotmail.com / ptirubber@hotmail.com Website <https://tuberry.net>



- ✓ ทนสารเคมี
- ✓ ทนต่อการหักงอ
- ✓ น้ำหนักเบา
- ✓ ทนสภาพแวดล้อมที่เย็น



NO.	ID (mm)	OD (mm)	Wall Thickness (mm)
50	11.0	16.0	2.50
51	11.0	18.0	3.50
52	12.0	15.0	1.50
53	12.0	16.0	2.00
54	12.0	17.0	2.50
55	12.0	18.0	3.00
56	12.0	19.0	3.50
57	12.0	20.0	4.00
58	15.0	20.0	2.50
59	16.0	19.0	1.50
60	16.0	20.0	2.00
61	16.0	22.0	3.00
62	18.0	24.0	3.00
63	19.0	24.0	2.50
64	19.0	25.0	3.00
65	19.0	28.0	4.50
66	19.0	32.0	6.50
67	20.0	28.0	4.00
68	22.0	28.0	3.00
69	22.0	32.0	5.00
70	25.0	32.0	3.50
71	25.0	33.0	4.00
72	25.0	35.0	5.00
73	25.0	38.0	6.50

Contact Us. Tel: 0 2489 5525 MB : 09 2656 8846 Technical Engineer Tel: 09 8253 9956

LINE@ @ptiglobal Email: ptig_sale2@hotmail.com / ptirubber@hotmail.com Website <https://tuberry.net>



- ✓ ทนสารเคมี
- ✓ ทนต่อการหักงอ
- ✓ น้ำหนักเบา
- ✓ ทนสภาพแวดล้อมที่เย็น



NO.	ID (mm)	OD (mm)	Wall Thickness (mm)
74	32.0	38.0	3.00
75	32.0	42.0	5.00
76	32.0	45.0	6.50
77	38.0	45.0	3.50
78	38.0	48.0	5.00
79	38.0	50.0	6.00
80	40.0	46.0	3.00
81	43.0	50.0	3.50
82	50.0	57.0	3.50
83	50.0	64.0	7.00
84	57.0	70.0	6.50
85	64.0	72.0	4.00
86	64.0	76.0	6.00

Contact Us. Tel: 0 2489 5525 MB : 09 2656 8846 Technical Engineer Tel: 09 8253 9956

LINE@ @ptiglobal Email: ptig_sale2@hotmail.com / ptirubber@hotmail.com Website <https://tuberry.net>